



## Shabbar Daud 9860284088 7020901740

## AN ISO 9001:2015 CERTIFIED COMPANY



Daud Compound, Shantinagar, NAGPUR - 440 002, (INDIA) e-mail : esskayplas@gmail.com website : www.uttamrope.com www.esskayplastics.com

Rope, Baler Twine, Rope Ladder

			11	133	1	AN IS						PANY								
	C	59				PP RO	PE	III A CONTRACT	DUU P		® गी.।	पी. रो।	Ţ	<b>GUA</b>			I) SIK	UNG	KUPE	
Daud Co			ar, NAGP	UR - 440 002	, (INDIA)			ES:	SK/		. म									
	e-mail	:esskayp	olas@gm	ail.com			ıg 👎	All S. S. Commen		163	е П	<u> </u>				<mark>ਦ ਇ</mark>	<u>50</u>	<mark>। र</mark> ु		
website	e : www.ess	kayplastic	cs.com, v	vww.uttamro	pe.com	Dural	ble		<b>PL</b>	ASI	fờ	काउ	5///							
			ESSKA	UTTAM R	OPE" MADE F	ROM 100% \	IRGIN P	OLYMERS		TECHN	ICAL DETA			Y UTTAN	ROPE	" MADE F				7
Rope Diameter	Load Usage Guide	Length p	oer Kg.	Weight of 1 Meter Rope	Weight of 110 Meter Rope	Weight of 220 Meter Rope	Breaking Load	Safe Load	S	Rope Diameter	Load Usage Guide	Length p	ber Kg.				Weight of 220 Meter Rope	Breaking Load	g Safe Load	
रस्सी व्यास	लोड उपयोग गाडड	the owner of the second s	and the second	१ मीटर रस्सी का वजन	११० मीटर रस्सी का वजन	२२० मीटर रस्सी का वजन	भार से तोडना	सुरक्षित लोड		रस्सी व्यास	लोड उपयोग गाइड						२२० मीटर रस्सी का वजन	भार से तोडना	सुरक्षित लोड	
mm	Kgs.				Kgs.	Kgs.	KGF	KGF	5	mm	Kgs.	Mtrs./ Kg	Feet/ Ko	g Gms.		Kgs.	Kgs.	KGF	KGF	
2	Till 8	550	1804	2	0.200	0.400	57	8		24	1000 To 1200	3.8	12.5	262		28.800	57.600	8179	1168	
2.5	Till 13	352	1155	3	0.320	0.630	89	13	K	26	1200 To 1400	3.3	10.8	307		33.800	67.600	9599	1371	
3	Till 18	244	802	4	0.450	0.900	128	18		28	1400 To 1600	2.8	9.2	356	4	39.200	78.400	11133	1590	
3.5	18 To 25	180	589	6	0.620	1.230	174	25		30	1600 To 1850	2.4	7.9	409		45.000	90.000	12780	1826	
4	25 To 30	138	451	7	0.800	1.600	227	32		32	1850 To 2100	2.1	6.9	465		51.200	102.400	14541	2077	
4.5	30 To 40	109	356	9	1.020	2.025	288	41		34	2100 To 2350	1.9	6.2	525		57.800	115.600	16415	2345	
5	40 To 50	88	289	11	1.250	2.500	355	51	55	36	2350 To 2650	1.7	5.6	589		64.800	129.600	18403	2629	
6	50 To 70	61	200	16	1.800	3.600	511	73	P	38	2650 To 3000	1.5	4.9	656		72.200	144.400	20505	2929	
7	70 To 100	45	147	22	2.450	4.900	696	99	5	40	3000 To 3250	1.4	4.6	727		80.000	160.000	22720	3246	Y
8	100 To 130	34	113	29	3.200	6.400	909	130		SUE	MERSI	BLE	PUN	IP RO	PE (	GREE		DUR	ROPE)	
9	130 To 160	27	89	37	4.050	8.100	1150	164										_		
10	160 To 200	22	72	45	5.000	10.000	1420	203						Lengin pe	r ny.				Meter Rope	
12	200 To 300	15	50	65	7.200	14.400	2045	292		रस्सी व्यास							177 2			
14	300 To 400	11	37	89	9.800	19.600	2783	398		mm										
16	400 To 500	8.6	28.2	116	12.800	25.600	3635	519						The second second						
18	500 To 650	6.8	22.3	147	16.200	32.400	4601	657		10				22	72	45			22.730	K
20	650 To 800	5.5	18.0	182	20.000	40.000	5680	811		12	200 To 30	0 204	15	15	50	65	14.4	00	32.730	
22	800 To 1000	4.5	14.8	220	24.200	48.400	6873	982		14	300 To 40	0 278	33	11	37	89	19.6	00	44.550	
	website   TECHN   Rope   Diameter   रससी व्यास   mm   2   2.5   3   3.5   4   4.5   5   6   7   8   9   10   12   14   16   18   20	Control Control Control Control   TECHNICAL DETA   Rope Diameter Load Usage Guide   रससी व्यास लोड उपयोग गाइड   mm Kgs.   2 Till 8   2.5 Till 13   3 Till 18   3.5 18 To 25   4 25 To 30   4.5 30 To 40   5 40 To 50   6 50 To 70   7 70 To 100   8 100 To 130   9 130 To 160   10 160 To 200   12 200 To 300   14 300 To 400   16 400 To 500   20 650 To 800	Daud Compound, Shantinaga (©): 942212720 e-mail : esskayp website : www.esskayplasticTECHNICAL DETAILS OF "Rope DiameterLoad Usage GuideLength aft erteth caute veeft cauteenis oyrain yrtssyfft fa aft emmKgs.Mtrs./ Kg2Till 85502.5Till 133523Till 182443.518 To 25180425 To 301384.530 To 40109540 To 5088650 To 7061770 To 100458100 To 130349130 To 1602710160 To 2002212200 To 3001514300 To 4001116400 To 5008.618500 To 6506.820650 To 8005.5	PLA     Daud Compound, Shantinagar, NAGP © : 9422127267, 98602 e-mail #esskayplas@gm website : www.esskayplastics.com, v     TECHNICAL DETAILS OF "ESSKAV Diameter     Coad Usage Guide   Length per Kg.     vtrtfl caure   erits grathy nuss   xRG fabritym ab relats     vtrtfl caure   erits grathy nuss   Mtrs./Kg   Feet/ Kg     2   Till 8   550   1804     2.5   Till 13   352   1155     3   Till 18   244   802     3.5   18 To 25   180   589     4   25 To 30   138   451     4.5   30 To 40   109   356     5   40 To 50   88   289     6   50 To 70   61   200     7   70 To 100   45   147     8   100 To 130   34   113     9   130 To 160   27   89     10   160 To 200   22   72     12   200 To 300   15   50	PLASTICS     Daud Compound, Shantinagar, NAGPUR - 440 002 (© : 9422127267, 9860284088 e-mail + esskayplas@gmail.com website : www.esskayplastics.com, www.uttamro     TECHNICAL DETAILS OF "ESSKAY UTTAM RO Diameter Guide Cuide	Daud Compound, Shantinagar, NAGPUR - 440 002, (INDIA) © : 9422127267, 9860284088     e-maill :esskayplas@gmail.com     website : www.esskayplastics.com, www.uttamrope.com     TECHNICAL DETAILS OF "ESSKAY UTTAM ROPE" MADE F     Rope Diameter   Load Usage Guide   Length per Kg.   Weight of 1 Meter Rope   Weight of 10 Meter Rope     vtth carrer   dis Gyain   JRft fareinJirr   9 Hilt tytem   940 Hilt tytem     mm   Kgs.   Mtrs./ Kg   Feet/ Kg   Gms.   Kgs.     2   Till 18   550   1804   2   0.200     2.5   Till 13   352   1155   3   0.320     3.   Till 18   244   802   4   0.450     3.5   18 To 25   180   589   6   0.620     4   25 To 30   138   451   7   0.800     4.5   30 To 40   109   356   9   1.020     5   40 To 50   88   289   11   1.250     6   50 To 70   61	CECECE Construction   PLASTICS     Daud Compound, Shantinagar, NAGPUR - 440 002, (INDIA) (@:: 9422127267, 9860284088 e-mail): esskayplas(ices.com, www.uttanrope.com)   Substruction     Daud Compound, Shantinagar, NAGPUR - 440 002, (INDIA) (@:: 9422127267, 9860284088) e-mail): esskayplas(ices.com, www.uttanrope.com)   Substruction     TECHNICAL DETAILS OF "ESSKAY UTTAM ROPE" MADE FROM 100% V Concerning and rest in a rown in	Корсание   Construction   Construction <th>Rope Diameter   Construction Construction   Construction Construction   Construction Construction   Construction Construction   Construction Construction   Construction   Constructin   Construction   Construc</th> <td>Construction   Press   Soft Strong Durable   Soft Strong Durable     Weight of: 42247267, 3860224088 email: esskayplastics.com, www.uttamrope.com   Soft Strong Durable   Soft Strong Durable   Soft Strong Durable     Weight of: 200   Veight of: 200   Nork   Soft Strong Durable   Soft Strong Durable     Technical Defails of the strong Dameler   Length per Kg. Weight of: 200   Weight of: 200   Breaking Meter Rope   Safe Load Load     Nameler   Guide   Length per Kg. Meter Rope   Weight of: 200   0.400   57   8     2.5   Till 13   352   1155   3   0.320   0.630   89   13     3.3   Till 18   244   802   4   0.450   0.900   128   18     3.5   18 To 25   180   589   6   0.620   1.230   174   25     4   25 To 30   138   451   7   0.800   1.600   227   32     4.5   30 To 40   109   356   9   1.020   2.010   355   51</td> <td>ССССССАНИСА   PP ROPE   Soft Storg Dual Compound, Shantinaga; NAGPUR- 440 002, (INDIA). (@:9422127267, 980024008) e-mail::esskayplas@gmail.com   PP ROPE   Soft Storg Dual Diab   Control Contentent Control Control Contentente Control Control Co</td> <td>Construction   Proprint   Proproprint   Proprint   Proprint</td> <td>Control   Control   <t< td=""><td>Construction   Construction   Construction&lt;</td><td>Construction   Properiod   Soft strong Dural   Construction   Constructio</td><td>Construction   Properiod   Soft Strong Durable   Soft</td><td>Example   Properiod   Soft Storg Duals   Soft Storg Storg Duals   Soft Storg Storg Storg Duals   Soft Storg Storg Storg Duals   Soft Storg Storg Storg Duals   Soft Storg Stor</td><td>Construction   Construction   Construction&lt;</td><td>Normaling   Normaling   <t< td=""><td>Conception   Properior   Soft strong   Distriction   Bit distretion   Bit distriction</td></t<></td></t<></td>	Rope Diameter   Construction Construction   Construction Construction   Construction Construction   Construction Construction   Construction Construction   Construction   Constructin   Construction   Construc	Construction   Press   Soft Strong Durable   Soft Strong Durable     Weight of: 42247267, 3860224088 email: esskayplastics.com, www.uttamrope.com   Soft Strong Durable   Soft Strong Durable   Soft Strong Durable     Weight of: 200   Veight of: 200   Nork   Soft Strong Durable   Soft Strong Durable     Technical Defails of the strong Dameler   Length per Kg. Weight of: 200   Weight of: 200   Breaking Meter Rope   Safe Load Load     Nameler   Guide   Length per Kg. Meter Rope   Weight of: 200   0.400   57   8     2.5   Till 13   352   1155   3   0.320   0.630   89   13     3.3   Till 18   244   802   4   0.450   0.900   128   18     3.5   18 To 25   180   589   6   0.620   1.230   174   25     4   25 To 30   138   451   7   0.800   1.600   227   32     4.5   30 To 40   109   356   9   1.020   2.010   355   51	ССССССАНИСА   PP ROPE   Soft Storg Dual Compound, Shantinaga; NAGPUR- 440 002, (INDIA). (@:9422127267, 980024008) e-mail::esskayplas@gmail.com   PP ROPE   Soft Storg Dual Diab   Control Contentent Control Control Contentente Control Control Co	Construction   Proprint   Proproprint   Proprint   Proprint	Control   Control <t< td=""><td>Construction   Construction   Construction&lt;</td><td>Construction   Properiod   Soft strong Dural   Construction   Constructio</td><td>Construction   Properiod   Soft Strong Durable   Soft</td><td>Example   Properiod   Soft Storg Duals   Soft Storg Storg Duals   Soft Storg Storg Storg Duals   Soft Storg Storg Storg Duals   Soft Storg Storg Storg Duals   Soft Storg Stor</td><td>Construction   Construction   Construction&lt;</td><td>Normaling   Normaling   <t< td=""><td>Conception   Properior   Soft strong   Distriction   Bit distretion   Bit distriction</td></t<></td></t<>	Construction   Construction<	Construction   Properiod   Soft strong Dural   Construction   Constructio	Construction   Properiod   Soft Strong Durable   Soft	Example   Properiod   Soft Storg Duals   Soft Storg Storg Duals   Soft Storg Storg Storg Duals   Soft Storg Storg Storg Duals   Soft Storg Storg Storg Duals   Soft Storg Stor	Construction   Construction<	Normaling   Normaling <t< td=""><td>Conception   Properior   Soft strong   Distriction   Bit distretion   Bit distriction</td></t<>	Conception   Properior   Soft strong   Distriction   Bit distretion   Bit distriction



























































No. 24, 1 kg 375 meters length. No. 12, 1 kg 750 meters length.

## रनबमर्रिबल पम्प ररनी SUBMERSIBLE PUMP ROPE



ESSKAY UTTAM GREEN COLOUR UV STABILISED ROPE SELECTION GUIDE FOR SUBMERSIBLE PUMPS सबमर्सिबल पम्प रस्सी के चयन के लिए मार्गदर्शिका								
PUMP SIZE IN HP पम्प का आकार	MAX WEIGHT INCLUDING	DEPTH OF WELL & ROPE SELECTION कुऍ की गहराई और रस्सी का चयन						
FROM - TO HP HP	PIPE अधिकतम वजन (पाइप मिलाकर)	30 MTRS / 100 F		50 MTRS / 165 FEET				
1 - 2	25 KGS	8mm	10mm	10mm	12mm			
3 - 5	40 KGS	10mm	10mm	10mm	12mm			
7.5 - 10	60 KGS	12mm	12mm	12mm	14mm			
12.5 - 20	70 KGS	14mm	14mm	14mm	14mm			





Γ							
	CE	RTIFICA	ΓE				
	This is to 0	Certify that the Management S	System of				
	E	SSKAY PLASTICS	6				
	DAUD COMPO	DUND, SHANTINAGAR, NAGP MAHARASHTRA, INDIA	UR-440002,				
	has been found to co	nform to the Quality Managemer	nt System standard:				
		ISO 9001:2015					
	This certificate is valid for the following scope of operations:						
	MANUFAC	TURING AND SUPPLY OF SY ROPES AND TWINES	NTHETIC				
	IAF Code: 14		NACE Code: 22.29				
	:: C	ertificate No :: IN108410	DA				
	Date of initial registration	Date of this Certificate	Recertification Due				
	25 March 2017	21 March 2023	24 March 2026				
	This Certific	cate remains valid subject to satisfactory	surveillance audits.				
	For verification and updated information concerning the This Certificate is the property of LMS Certifications F						
	مرخز الإمارات العالمي للاعتماد Enfrates International Accreditation Center CB-QMS-006	1, Ananddham, C	essments.com				